

2MP AHD HA-DVR-2108-L

- H.265 dual-stream video compression
- Supports AHD/HQA/CVI/CVBS/IP video inputs
- Max 10 channels IP camera inputs, each channel up to 6MP; Max 40Mbps incoming bandwidth
- Long transmission distance over coax cable
- Supports 1 SATA HDD, up to 6TB



SYSTEM OVERVIEW

With the surveillance operators pursuing to HD/UHD which further adds the storage and transmission cost, H.265 has been released to incredibly decrease the required bitrate while ensuring the video quality in realizing high resolution surveillance such as 4MP/4K.

The Lite Series is designed for high cost performance and quality. The range offers a great solution for users facing budget constraints who both require quality and performance. And with the adoption of Smart H.265, the series improves encoding efficiency, saving on bandwidth/storage costs, and significantly reducing the Total Cost of Ownership (TCO).

FUNCTIONS

Smart H.265

Smart Codec, H.265 can reduce up to 90% bit rate and storage requirements compared with H.264 without having to invest in new cameras.

AHD/HQA/CVI/CVBS/IP Auto-detect

The DVR can auto recognize the signal of front-camera without any setting. It makes operation more friendly and convenient.

6MP Resolution

The DVR supports up to 6MP HD resolution (2880 x 1920) IPC input for recording, live viewing.

Coaxial Audio/Upgrade/Alarm

The integrated design can reduce wiring troubles which makes it much more cost-effective and convenient for installation.

Long Distance Transmission

The DVR system supports long distance transmission over coaxial cable and UTP, max. 700m for 4K/4MP, 800m for 1080P and 1200m for 720P.

Smart Search

This function helps you get more motion detect video during a short time through drawing a region when playback. It is very useful when an emergency occurs.

Perfect Image Quality

High performance chip provides perfect image quality with better color reproduction.

P2P

Monitor at anytime and anywhere. Easily and conveniently manage the device.

Technical Specification

System

Main Processor	Embedded Processor
Operating System	Embedded LINUX

Video and Audio

Analog Camera Input	8 Channel, BNC
HD Camera	1080P@25/30, 720P@25/30fps
CVBS Camera	PAL/NTSC
IP Camera Input	8+2, each channel up to 6MP
Audio In/Out	1/1, RCA
Two-way Talk	Reuse audio in/out, RCA

Recording

Video Compression	H.265 / H.264
Resolution	1080N, 720P, 960H, D1, CIF
Record Rate	Main Stream: the 1st channel 1080N/720P(1~25/30fps), others 1080N/720P(1~15fps) 960H/D1/CIF (1~25/30fps) Sub stream:CIF (1~7fps)
Video Bit Rate	32Kbps ~ 4096Kbps Per Channel
Record Mode	Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval	1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec
Audio Compression	AAC(only for the 1st channel), G.711A, G.711U, PCM
Audio Sample Rate	8KHz, 16 bit Per Channel
Audio Bit Rate	64Kbps Per Channel

Display

Interface	1 HDMI ,1 VGA
Resolution	1920×1080, 1280×1024, 1280×720
Multi-screen Display	When IP extension mode not enabled: 1/4/8/9 When IP extension mode enabled: 1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

Network

Interface	1 RJ-45 Port (100M)
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, SNMP, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, P2P
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF Conformant

Video Detection and Alarm

Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis
Alarm input	N/A
Relay Output	N/A

Playback and Backup

Playback	1/4/9
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network

Storage

Internal HDD	1 SATA Port, up to 6TB capacity
--------------	---------------------------------

Auxiliary Interface

USB	2 USB 2.0
RS485	1 Port, for PTZ Control

Electrical

Power Supply	DC12V/1.2A
Power Consumption (without HDD)	<10W

Construction

Dimensions	260×236×48mm(10.2"×9.3"×1.9")
Net Weight (without HDD)	0.9kg (2.0lb)
Gross Weight	1.6kg (3.5lb)
Installation	Desktop installation

Environmental

Operating Conditions	-10°C ~ +45°C (+14°F ~ +113°F), 10~90% RH
Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0~90% RH




Certifications

Certifications	BIS Certified
----------------	---------------


Ordering Information

Type	Part Number	Description
8 Channel DVR	HA-DVR-2108-L	8ch, 2MP DVR, 1 SATA, H.265

Dimensions (mm)



Rear Panel



1	VIDEO IN	6	RS485 Interface
2	AUDIO IN, RCA Connector	7	USB Interface
3	AUDIO OUT, RCA Connector	8	DC 12V Power Input
4	HDMI Interface	9	VGA Interface
5	Network Interface		

For more information,

www.partnerconnect.honeywell.com

Call: 1-800-103-0339

Email: HoneywellSecurity&Fire@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002

www.honeywell.com

© 2019 Honeywell International Inc.

2MP AHD
HA-DVR-2108-L

Honeywell