# HN-PHP15A

## Horn Loudspeaker

HN-PHP15A/ is a 15W full range horn loudspeaker for high Power handling and reliability. Taps on the primary winding allow different power setting. Housing is made of study ABS fire resistance material with strength and low weight. With its the aesthetical and style design, it can be installed in various applications such as train station, harbors, plaza, police station government administration, tourist destinations, educational institute, transport hubs, and office building. The horn is attached with strong and adjustable mounting brackets which help to accurately direct the sound beam. The loudspeaker is CE complied.



#### **ABOUT THE PRODUCT**

The speaker enclosure is fully made with ABS with glossy finish.

#### **CERTIFICATIONS AND APPROVAL**

CE Complied/IP 66

### **FEATURES AND BENEFIT**



HIGH IMPACT FIRE RESISTANCE ABS MATERIAL



LOWER
MAINTENANCE COST





#### **INSTALLATION DETAILS/DIMENSIONS**


 $\frac{\text{HN-PHP15A}}{\text{is a horn loudspeaker which can be Used to easily adjustable mounting brackets in any Surface to accurately direct the sound beam. It has Three power tapping (15/7.5/3.75W) with built in 100V transformer.$ 


#### **DIMENSIONS**

#### THREE-VIEW DIAGRAM



#### Circuit Diagram:





## **TECHNICAL SPECIFICATIONS**

SYSTEM PERFORMANCE	
Frequency Range (-10dB)	350Hz – 8 KHz
Nominal Dispersion	140°(H) X 50° (V)
Rated Impedance	667 <b>Ω</b> at 15 W
Long-Term Power Handling	15 W (22W peak)
Sensitivity (SPL / 1 W @1m)	104 dB SPL
Maximum SPL @1m	116 dB SPL
Rated Input Voltage	100 V/ 70V
Transformer Taps (100V)	15 W / 7.5W / 3.75 W
PHYSIC	
Enclosure	ABS
Environmental	Outdoor uses, IP 66
Operating Temperature	-25° C to 55° C
Storage Temperature	-40° C to 70° C
Relative Humidity	<95%
Connectors	4 CORE Flexible wire having 4 connection of Com, 15W, 7.5W, & 3.75W
Suspension/Mounting	U Shape mounting clamp is fixed in speaker and can be mount easily on any wall with 3 holes in clamp.
Dimensions	Length- 221mm Width- 164mm Height- 235 mm
Colour	White( RAL 9003)
Net Weight	(1.38kg)
Shipping Weight	(1.68Kg)

#### For more information,

www.honeywellbuildings.in Call: 000-8000-502167 Email: HBT-IndiaBuildings@Honeywell.com

#### Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43, Block C, Sushant Lok Phase - I, Gurgaon - 122 002.



