# **HN-IA240**

## **I** Power Amplifier

HN-IA240 is a high efficient 240W Power/Booster amplifier provides audio signal amplification for public address and voice alarm system, It is reliable, efficient and light in weight.

### **FEATURES AND BENEFIT**



## AND THERMAL PROTECTION

## **TECHNICAL SPECIFICATIONS**

**INDICATIONS** 

ELECTRICAL	
Mains power supply	180~250 Volts AC   50 Hz
Power Consumption	600 VA
Amplifier topology	Class D >90% efficiency
Frequency response	70 Hz to 20 KHz
THD + N @ 1 KHz	0.1%
Signal input / Output	Balanced Line in - LineOut  100 V signal input
SNR (dB)	102
Dynamic range	93dB
Power Output	240 watts   100 Volt speaker output - Phoenix connector
Damping factor @ 8 Ohm	300
Protection	Output Short-circuit   Thermal shut-down
Dimension (mm)	95.2 H x 431.8 W x 304.8 D
Operating Temperature & Humidity	-10°c to 50°c @ 90% relative humidity (non condensing)
Cooling	Natural dissipation through heat sink   Very low heat dissipation because of high efficiency class D technology
Weight	5.2 Kg
Certifications	CE Complied

#### For more information,

www.honeywellbuildings.in Call: 000-8000-502167 Email: HBT-IndiaBuildings@Honeywell.com

#### Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43, Block C, Sushant Lok Phase - I, Gurgaon - 122 002.

HN - IA240 | 01 | 09/21 © 2021 Honeywell International Inc.





#### TURE IS WHAT WE **MAKE IT**

